

AMBUJET S

Portable suction device



Space-saving suction device to be used to remove fluids from the airway or respiratory support system. The device creates a negative pressure that draws fluids through disposable tubing that is connected to the collection container. Can be equipped with a 10g fastener.

Specific features

- Low weight and size
- Easy visualization of the selected vacuum thanks to the LED lights and the slope of monitoring surface
- Used together with the quick release fastener, the device is always ready for use
- Classification ISO High Vacuum/ High Flow
- Wide base to increase stability
- The shell provides protection to the suction unit
- Adjustment knob easy and practical to use
- Mechanism to fix the canister for increased safety
- Available with different type of canisters

Standard Equipment

- Battery
- canister
- Disposable patient tube 1,8 m
- Shoulder strap for easy transport
- 10 g Fastener (many versions available)

Compliant with

ISO 10079-1
EN 1789

Technical data

Dimensions	380x215x180 ± 5 mm
Dimensions w/fastener	380x240x180 ± 5 mm
Weight with without fastener	3,15 ± 0,1 kg
Vacuum Range	Da 50 a 550 mmHg
Flow (free flow)	32 l/min
Noise level	70 db
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75 A max; 12VDC 33W max
IP Grade	IP12
Battery	12V DC Ni-MH
Battery operating time	Max 45-60min at free flow
Battery recharging time	5 h
Operation mode	30 min. ON, 30 min. OFF
Container capacity	1000 ml
Patient tube lenght	1,8 m
Operating temp.	From 0°C to +45°C
Storage temp.	From - 40°C to +70°C
Humidity	From 0 to 95%

Med. Dev. CE marked according to Dir. 93/42/CE
AMBUJET S



Rev.0 (14/03/2018)

UNCHECKED COPY – further revisions will be available on <http://support.spencer.it>
Spencer Italia S.r.l. Sala Baganza (PR) Italia Tel. +39.0521.541111 Fax +39.0521.541222

spencer.it